

## Safety Data Sheet dated 10/10/2022, version 4.0 This version cancels and substitutes any previous version

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MOKA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Coffee Machine Cleaner

1.3. Details of the supplier of the safety data sheet

Company:

ERRECÓM SPA

Via Industriale, 14

Corzano (BS) Italy

Tel. +39 030/9719096

Competent person responsible for the safety data sheet:

lab@errecom.it

1.4. Emergency telephone number

+39 02-6610-1029 Poison Control Center Niguarda Ca' Granda - Milano - ITALY

### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2, Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eve irritation.

Precautionary statements:

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Special Provisions:** 

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None



2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards:

No other hazards

### **SECTION 3: Composition/information on ingredients**

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number		Classification
>= 7% - < 10%	glycolic acid	CAS: EC:	79-14-1 201-180-5 01-21194855 79-17-XXXX	2.16/1 Met. Corr. 1 H290  3.1/4/Inhal Acute Tox. 4 H332  3.2/1B Skin Corr. 1B H314 Specific Concentration Limits: C >= 15%: Skin Corr. 1B H314 5% <= C < 15%: Skin Irrit. 2 H315 5% <= C < 15%: Eye Irrit. 2 H319
>= 2.5% - < 5%	ethanol	Index number: CAS: EC: REACH No.:	603-002-00-5 64-17-5 200-578-6 01-21194576 10-43-XXXX	<u> </u>
>= 0.25% - < 0.5%	propan-2-ol	Index number: CAS: EC: REACH No.:	603-117-00-0 67-63-0 200-661-7 01-21194575 58-25-XXXX	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336

### **SECTION 4: First aid measures**

4.1. Description of first aid measures

In case of skin contact:

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).



Treatment:

None

### **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains

Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store the product between + 0 °C / + 32 °F and + 40 °C / + 104 °F.

Keep away from food, drink and feed.

Incompatible materials:

See subsection 10.5

Instructions as regards storage premises:



Adequately ventilated premises.

7.3. Specific end use(s)

Information not available.

### **SECTION 8: Exposure controls/personal protection**

```
8.1. Control parameters
```

ethanol - CAS: 64-17-5

ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr

AGW - TWA(8h): 380 mg/m3, 200 ppm - STEL(15min): 1520 mg/m3, 800 ppm MAK - TWA(8h): 380 mg/m3, 200 ppm - STEL(15min): 1520 mg/m3, 800 ppm

VLA - STEL(15min): 1910 mg/m3, 1000 ppm

VLEP - TWA(8h): 1900 mg/m3, 1000 ppm - STEL(15min): 9500 mg/m3, 5000 ppm

WEL - TWA(8h): 1920 mg/m3, 1000 ppm TLV (GR) - TWA(8h): 1900 mg/m3, 1000 ppm GVI - TWA(8h): 1900 mg/m3, 1000 ppm

NDS - TWA(8h): 1900 mg/m3

NPHV - TWA(8h): 960 mg/m3, 500 ppm - STEL(15min): 1920 mg/m3

TLV - TWA(8h): 1000 mg/m3

TLV (CZ) - TWA(8h): 1000 mg/m3, 522 ppm - STEL(15min): 3000 mg/m3, 1566 ppm TLV (EST) - TWA(8h): 1000 mg/m3, 500 ppm - STEL(15min): 1900 mg/m3, 1000 ppm

propan-2-ol - CAS: 67-63-0

ACGIH - TWA: 200 ppm - STEL: 400 ppm

MAK - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm VLA - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm

VLEP - STEL(15min): 980 mg/m3, 400 ppm

WEL - TWA(8h): 999 mg/m3, 400 ppm - STEL(15min): 1250 mg/m3, 500 ppm TLV - TWA(8h): 980 mg/m3, 400 ppm - STEL(15min): 1225 mg/m3, 500 ppm

NDS - TWA(8h): 900 mg/m3 - STEL(15min): 1200 mg/m3

NPHV - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3

MV - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 2000 mg/m3, 800 ppm GVI - TWA(8h): 999 mg/m3, 400 ppm - STEL(15min): 1250 mg/m3, 500 ppm

TLV (CZ) - TWA(8h): 500 mg/m3, 200 ppm - STEL(15min): 1000 mg/m3, 400 ppm TLV (EST) - TWA(8h): 350 mg/m3, 150 ppm - STEL(15min): 600 mg/m3, 250 ppm

#### **DNEL Exposure Limit Values**

glycolic acid - CAS: 79-14-1

Worker Industry: 9.2 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 9.2 mg/m³ - Consumer: 2.3 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 1.53 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 58 mg/kg - Consumer: 29 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 0.75 mg/kg - Exposure: Human Oral - Frequency: Long Term (repeated) ethanol - CAS: 64-17-5

Worker Industry: 1900 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 950 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 343 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

propan-2-ol - CAS: 67-63-0

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects



```
Worker Industry: 500 mg/m<sup>3</sup> - Consumer: 89 mg/m<sup>3</sup> - Exposure: Human Inhalation -
             Frequency: Long Term, systemic effects
             Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal -
             Frequency: Long Term, systemic effects
PNEC Exposure Limit Values
      glycolic acid - CAS: 79-14-1
             Target: Fresh Water - Value: 0.0312 mg/L
             Target: Marine water - Value: 0.0031 mg/L
             Target: Freshwater sediments - Value: 0.115 mg/kg
             Target: Marine water sediments - Value: 0.0115 mg/kg
             Target: Soil (agricultural) - Value: 0.007 mg/kg
             Target: Aquatic, periodic release - Value: 0.312 mg/L
             Target: Microorganisms in sewage treatments - Value: 7 mg/L
             Target: Secondary poisoning - Value: 11.66 mg/kg
      ethanol - CAS: 64-17-5
             Target: Fresh Water - Value: 0.96 mg/L
             Target: Marine water - Value: 0.79 mg/L
             Target: Freshwater sediments - Value: 36 mg/kg
             Target: Marine water sediments - Value: 2.9 mg/kg
             Target: Aquatic, periodic release - Value: 2.75 mg/L
             Target: Microorganisms in sewage treatments - Value: 580 mg/L
             Target: Secondary poisoning - Value: 0.72 mg/kg
             Target: Soil (agricultural) - Value: 0.63 mg/kg
      propan-2-ol - CAS: 67-63-0
            Target: Fresh Water - Value: 140.9 mg/L
Target: Marine water - Value: 140.9 mg/L
             Target: Freshwater sediments - Value: 552 mg/kg
             Target: Aquatic, periodic release - Value: 140.9 mg/L
             Target: Microorganisms in sewage treatments - Value: 2251 mg/L
             Target: Marine water sediments - Value: 552 mg/kg
             Target: Soil (agricultural) - Value: 28 mg/kg
8.2. Exposure controls
Eye protection:
      Protective airtight goggles (ref. Standard EN 166).
Protection for skin:
      Not needed for normal use.
Protection for hands:
      One-time gloves.
      Suitable material:
      NBR (nitrile rubber).
      NR (natural rubber, natural latex).
      Material thickness: minimum 0.12 mm.
      Break through time: > 480 min
      Take note of the information given by the producer concerning permeability and break
      through times, and of special workplace conditions (mechanical strain, duration of contact).
Respiratory protection:
      Not needed for normal use.
Thermal Hazards:
      None
Environmental exposure controls:
      None
Appropriate engineering controls:
```

None



### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Colourless		
Odour:	characteristic		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point:	63 ° C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	2.05		
Kinematic viscosity:	N.A.		
Solubility in water:	total		
Solubility in oil:	partial		
Partition coefficient n-octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		
Density and/or relative density:	1.03 g/mL (+20°C / +68°F)		
Relative vapour density:	N.A.		

Particle characteristics:

l Particle size: I N.A. I I
-----------------------------

#### 9.2. Other information

No other relevant information

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

Under normal use and storage conditions, no hazardous reactions are expected.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Bases, amines, alkali metals, permanganates.

Strong oxidizing agents.

10.6. Hazardous decomposition products

No data available

### **SECTION 11: Toxicological information**



11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product:

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure

Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

glycolic acid - CAS: 79-14-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation Mist - Species: Rat 3.6 mg/L - Notes: (aerosol)

b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin Positive

c) serious eye damage/irritation:

Test: Eye Corrosive - Route: Eyes Positive

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin Negative

e) germ cell mutagenicity:

Test: Respiratory Sensitization Negative

Test: Mutagenesis Negative

f) carcinogenicity:

Test: Carcinogenicity Negative

g) reproductive toxicity:

Test: Reproductive Toxicity Negative

ethanol - CAS: 64-17-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Mouse > 20 mg/L - Duration: 4h

propan-2-ol - CAS: 67-63-0

a) acute toxicity:



Test: LD50 - Route: Oral - Species: Rat 4710 mg/kg Test: LD50 - Route: Skin - Species: Rat 12800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 72.6 mg/L - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit 6290 mg/kg

#### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Not classified for environmental hazards

Based on available data, the classification criteria are not met

#### glycolic acid

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 115 mg/L - Duration h: 96 - Notes: US EPA E 72-2 Endpoint: EC50 - Species: Daphnia 99.6 mg/L - Duration h: 48 - Notes: OECD TG 202 Endpoint: LC50 - Species: Algae 15.3 mg/L - Duration h: 72 - Notes: OECD TG 201

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish 91 mg/L Endpoint: NOEC - Species: Daphnia 71 mg/L Endpoint: NOEC - Species: Algae 14 mg/L

#### ethanol

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 11200 mg/L - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 12300 mg/L - Duration h: 48 - Notes: Species:

Daphnia magna

Endpoint: EC50 - Species: Algae > 275 mg/L - Duration h: 72 - Notes: Species:

Chlorella vulgaris

### propan-2-ol

a) Aquatic acute toxicity:

Endpoint: EC0 - Species: Fish 10000 mg/L - Duration h: 48 - Notes: Pimephales

promelas

Endpoint: LC50 - Species: Fish > 1400 mg/L - Duration h: 96 - Notes: Lepomis

macrochirus

Endpoint: LC50 - Species: Fish 6550 mg/L - Duration h: 96 - Notes: Pimephales promelas

### 12.2. Persistence and degradability

glycolic acid - CAS: 79-14-1

Biodegradability: Readily biodegradable - Test: Modified Sturm Test - Notes: OECD TG 301B / 301D

ethanol - CAS: 64-17-5

Biodegradability: Readily biodegradable - Test: Solubility in water - Notes: 1000 - 10000 mg/L

propan-2-ol - CAS: 67-63-0

Biodegradability: Readily biodegradable

#### 12.3. Bioaccumulative potential

glycolic acid - CAS: 79-14-1

Bioaccumulation: Not bioaccumulative

ethanol - CAS: 64-17-5

Bioaccumulation: Not bioaccumulative - Test: Kow - Partition coefficient 0.350000-

propan-2-ol - CAS: 67-63-0

Bioaccumulation: Not bioaccumulative - Test: Kow - Partition coefficient 0.05



12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

None

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

### **SECTION 14: Transport information**

14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

14.6. Special precautions for user

ŃΑ

14.7. Maritime transport in bulk according to IMO instruments

N.A.

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)



Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3
Restriction 40

Restrictions related to the substances contained:

Restriction 75

Where applicable, refer to the following regulatory provisions:

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

#### **SECTION 16: Other information**

Full text of phrases referred to in Section 3:

H290 May be corrosive to metals.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method



This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no quarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.